

GÖLZ FT180 • FT190 • FT200

- 0° - 45° adjustable, with cutting control fence
- Angle stop (FT190/200)
- electric water pump (FT190/200)
- Fold-away legs (FT200)
- FT 180/ FT 190 and FT 200 incl. diamond blade SF 20



Technical data	FT180	FT190	FT200
Max. cutting depth	35 mm	40 mm	40 mm
Max. cutting length	350 mm	450 mm	600 mm
Max. blade-Ø	180 mm	200 mm	200 mm
Arbor hole	25,4mm	25,4mm	25,4mm
Motor	230V, 50Hz	230V, 50Hz	230V, 50Hz
Power input/output	0,55 kW / 0,65 kW	0,65 kW / 0,78 kW	0,65 kW / 0,78 kW
weight	13 kg	22 kg	34 kg
Dimensions	420x470 mm	710x450x400	960x560x470
Order No	0281 180 1000	0281 190 1000	0281 200 1000

Accessories	Order No
Lateral extension arm, FT200	0281 200 1010
Water pump G1, FT190/FT200	0281 350 0222

GÖLZ TABLE SAWS ST85A • ST100A • ST120A • ST150A • ST200A

- Very light aluminium construction = -30% weight against old model
- Guide shafts with ball bearing
- Lateral stop (angle cutting device available as accessories)
- Electric water pump
- Handwheel to adjust the cutting depth
- Cutting head adjustable till 45°
- Supporting table removeable for cleaning
- Transport handles
- Wheels for site and loading help (ST65A - ST 120A)



Technical data	ST85A	ST100A	ST120A	ST150*	ST200*
Max. cutting depth	110 mm	110 mm	110 mm	110 mm	150 mm
Max. cutting length	850 mm	1000 mm	1200 mm	1500 mm	2000 mm
Max. blade-Ø	350 mm	350 mm	350 mm	350 mm	450 mm
Arbor hole	25,4mm	25,4mm	25,4mm	25,4mm	25,4mm
Motor	230V, 50Hz	230V, 50Hz	230V, 50Hz	230V, 50Hz	230V, 50Hz
Power in/out	2,2 kW / 3 HP	2,2 kW / 3 HP	2,2 kW / 3 HP	2,2 kW / 3 HP	2,2 kW / 3 HP
weight	66 kg	79 kg	115 kg	180 kg	260 kg
Dimensions	127x66x77	140x66x77	160x66x77	197x66x77	250x88x77
Order No	0281 085 4000	0281 100 4000	0281 120 4000	0281 150 1000	0281 200 2020

* Also available with 3-phase motor!

Accessories	Order No
Angle stop, adjustable	0281 085 0100
Lateral roller extension arm, 1m long, 54cm wide, for ST85	0281 085 0101
Lateral flat extension arm, 55cm long, 50cm wide, for ST85	0281 085 0102
Laser pointer with holder	0281 085 0104
Water pump G1	0281 350 0222

GÖLZ STA350

- Cutting head adjustable and slewable up to 45°
- Cutting table ball beared for exact cutting
- Angle stop
- **incl. Professional laser cutting device!**
- Removeable and adjustable legs
- Electric water pump
- Transport handles
- Transport wheels

Technical data	STA350
Max. cutting depth	110 mm
Max. cutting length	800 mm
Max. blade-Ø	350 mm
Arbor hole	25,4mm
Motor	230V, 50Hz
Speed range	2650 rpm
Power	2,2 kw / 3 HP
Cutting table	600 x 600 mm
Weight	68 kg
Dimensions	1180x810x710
Oder No	0281 350 2000



GÖLZ STA85S

- Cutting head adjustable up to 45°
- Angle stop
- **Inclusive professional laser cutting device!**
- Removeable and adjustable legs
- Electric water pump
- Transport wheels

Technical data	STA85S
Max. cuttingdepth	110 mm
Max. cuttinglength	850 mm
Max. blade-Ø	350 mm
Arbor hole	25,4mm
Motor	230V, 50Hz
Power	2,2 kw / 3 HP
Weight	80 kg
Dimensions	770x1580x1350
Oder No	0281 085 5000



Accessories	Order No
Flat bracket	0281 085 0305
Roll bracket	0281 085 0306

GÖLZ BS350 • BS350L

- Cutting head adjustable
- Removable blade guard for changing diamond blades quickly
- Angle stop
- Cart with ball-bearing steel rollers ensure precise cutting
- Removable legs
- Electric water pump

Technical data	BS350	BS350L
Max. cutting depth	125 mm	125/150 mm
Max. cutting length	500 mm	650 mm
Max. blade-Ø	350 mm	350/400 mm
Arbor hole	25,4mm	25,4mm
Motor	230V, 50Hz, IP54	230V, 50Hz, IP54
Shaft speed	2650 rpm	2650 rpm
Power	2,2 kW / P1 (3 HP)	2,2 kW / (3 HP)
Cart	325x445, steel	410x480, steel
Weight	59 kg	85 kg
Dimensions	950x530x1270	1120x600x1400
Oder No	0281 351 1100	0281 401 1000



Accessories	Order No
45°-angle guide fitting (Jolly)	0281 045 0900
Set of wheels for BS350	0281 350 0901
Water pump G1	0281 350 0222

GÖLZ ST350 • ST350L

- High quality cast cart
- Transport wheels and handles
- Cart with ball-bearing steel rollers ensure precise cutting
- Cutting head adjustable
- Removable, galvanized water tub
- Electric water pump

Technical data	BS350	BS350L
Max. cutting depth	125 mm	125/150 mm
Max. cutting length	500 mm	650 mm
Max. blade-Ø	350 mm	350/400 mm
Arbor hole	25,4mm	25,4mm
Motor	230V, 50Hz, IP54	230V, 50Hz, IP54
Power	2,2 kW / 3HP	2,2 kW / 3HP
Speed range	2650 rpm	2650 rpm
Cart L x W	321x435, cast	400x480, cast
Weight	59 kg	85 kg
Dimensions	950x530x1270 mm	1120x600x1330 mm
Oder No	0281 350 1000	0281 400 1000



Accessories	Order No
45°-angle guide fitting (Jolly)	0281 045 0900
Water pump G1	0281 350 0222

GÖLZ ST450 • ST450S

- High quality cast cart
- Parallel cutting head guide
- Electric water pump
- Removeable blade guard for changing diamond blades quickly
- Cart with ball bearing steel rollers ensure precise cutting
- Removeable galvanized water tub

Technical data	ST450	ST450S
Max. cutting depth	175 mm	175 mm
Max. cutting length	650 mm	650 mm
Max. blade-Ø	450 mm	450 mm
Arbor hole	25,4mm	25,4mm
Motor	230V, 50Hz, IP54	400V, 50Hz, 16A, IP54
Power	2,2 kW / 3 HP	3,0 kW / 4 HP
Shaft speed	2650 rpm	2650 rpm
Cart L x W	400x480, cast	400x480, cast
Weight	106 kg	106 kg
Dimensions	1130x590x1370	1130x590x1370
Order No	0281 450 1000	0281 450 2000



Accessories	Order No
45°-angle guide fitting (Jolly)	0281 045 0900
Water pump G1	0281 350 0222

GÖLZ BS650 • BS900

- Torsion free frame with jack rings
- Cutting head spring mounted
- Adjustable by manual lever
- 4 transport wheels, 2 of them are lockable
- Removeable, galvanized water tub



BS650



BS900

Technical data	BS650	BS900
Max. cutting depth	260 mm	370 mm
Max. cutting length	500 mm	600 mm
Max. blade-Ø	650 mm	900 mm
Arbor hole	60 mm	60 mm
Motor	400V, 50Hz, 16A	400V, 50Hz, 32A
Power	5,5 kW / 7,5HP, IP54	7,5 kW / 10HP, IP54
Shaft speed	1020 rpm	990 rpm
Cart Lx W	610x670 mm	610x840 mm
Flange-Ø	120mm	160mm
Weight	230 kg	280 kg
Dimensions	1600x800x1200	2000x1100x1550
Order-No	0282 650 2006	0282 900 2010

Accessories	Order No
Water pump G3	0282 650 0179